



**ASI 502 Black**

<b>Section 1: Product and Company Identification</b>	
American Sealants, Inc. 9190 Yeager Ln Fort Wayne, Indiana 46809 Phone: 260-489-0728 Fax: 260-489-0519	<b>Emergency Phone Number</b> Infotrac: +1-800-535-5053 (Within US) Infotrac: +1-352-323-3500 (Outside US)
<b>Product Identifier:</b> ASI 502 Black <b>Recommended Use:</b> Adhesive <b>Restrictions on Use:</b> None known	

<b>Section 2: Hazard(s) Identification</b>	
<b>GHS Classification:</b>	Not a hazardous substance or mixture.
<b>GHS Label Elements</b>	
Symbol(s):	None.
Signal Word:	None.
Hazard Statement(s):	None known.
<b>Precautionary Statement(s)</b>	
Prevention:	Use only outdoors or in a well-ventilated area. Avoid release to the environment.

<b>Section 3: Composition/Information on Ingredients</b>		
Substance/Mixture:	Mixture	
Chemical Nature:	Silicone Elastomer	
<b>Hazardous Ingredients</b>		
<u>CAS</u>	<u>Component</u>	<u>Percent</u>
7631-86-9	Silicon dioxide	5 - <10
13463-67-7	Titanium dioxide	1 - <5
7429-90-5	Aluminum	1 - <5

# SAFTEY DATA SHEET

Product Identifier: ASI 502 Black

Document #: SDS 006

Revision: 2

1333-86-4	Carbon black	0.1 - <1
-----------	--------------	----------

## Section 4: First-Aid Measures

Inhalation:	IF INHALED: Remove to fresh air. Get medical attention if symptoms occur.
Skin Contact:	IF ON SKIN: Wash with soap and water as a precaution. Get medical advice/attention if symptoms occur.
Eye Contact:	IF IN EYES: Flush eyes with water as a precaution. If eye irritation develops and persists: Get medical advice/attention.
Ingestion:	If swallowed, DO NOT induce vomiting. Get immediate medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed:	None known
Protection of first-aiders:	No special precautions are necessary for first aid responders
Notes to physician:	Treat symptomatically and supportively

## Section 5: Fire-Fighting Measures

Suitable Extinguishing Media:	Use carbon dioxide, regular dry chemical, alcohol-resistant foam or water.
Unsuitable Extinguishing Media:	None known.

### Specific Hazards Arising from the Chemical

Exposure to combustion products may be a hazard to health.

Hazardous Combustion Products:	Carbon oxides, silicon oxides, formaldehyde, and metal oxides
--------------------------------	---

Special Protective Equipment and Precautions for Firefighters:	Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.
--	--

Specific extinguishing methods:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
---------------------------------	---

# SAFTEY DATA SHEET

Product Identifier: ASI 502 Black

Document #: SDS 006

Revision: 2

## Section 6: Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Follow safe handling advice and personal protective equipment recommendations.

Environment Precautions:

Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and Materials for Containment and Cleaning Up:

Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

## Section 7: Handling and Storage

Technical Measures:

See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation:

Use only with adequate ventilation.

Advice on safe handling:

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment.

Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage:

Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid:

Do not store with the following product types:  
Strong oxidizing agents

## Section 8: Exposure Controls/Personal Protection

### Component Exposure Limits

CAS	Component	Exposure Limits
7631-86-9	Silicon dioxide	OSHA Z-3: 20 million particles/ft <sup>3</sup> (Silica) TWA (dust); 80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica) TWA (dust)

# SAFTEY DATA SHEET

Product Identifier: ASI 502 Black

Document #: SDS 006

Revision: 2

13463-67-7	Titanium dioxide	<p><b>NIOSH REL:</b> 6 mg/m3 (Silica) TWA  <b>ACGIH:</b> 10 mg/m3 TWA  <b>OSHA Z-1:</b> 15 mg/m3 TWA (total dust)  <b>ACGIH:</b> 1 mg/m3 TWA (respirable fraction)</p>
7429-90-5	Aluminum	<p><b>OSHA Z-1:</b> 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)  <b>NIOSH REL:</b> 5 mg/m3 TWA (respirable fraction); 10 mg/m3 TWA (total)  <b>ACGIH:</b> 3 mg/m3 TWA (inhalable fraction)</p>
1333-86-4	Carbon black	<p><b>OSHA Z-1:</b> 3.5 mg/m3 TWA  <b>NIOSH REL:</b> 3.5 mg/m3 TWA</p>
<p><b>These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.</b></p>		
<p>Silicon dioxide  Titanium dioxide  Carbon black</p>		
<b>Engineering measures:</b>		<p>Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m3 - respirable particles, 10 mg/m3 - inhalable particles.</p>
<b>Personal Protective Equipment</b>		
Respiratory protection		<p>General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.</p>
Hand Protection		
Remarks		Wash hands before breaks and at the end of workday.
Eye Protection		Wear the following personal protective equipment: Safety glasses
Skin and body protection		<p>Skin should be washed after contact.  Ensure that eye flushing systems and safety showers are located close to the working place.  When using do not eat, drink or smoke.</p>
Hygiene measures		<p>Wash contaminated clothing before re-use.  These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.</p>

<b>Section 9: Physical and Chemical Properties</b>

# SAFTEY DATA SHEET

Product Identifier: ASI 502 Black

Document #: SDS 006

Revision: 2

<b>Physical State:</b> Liquid	<b>Appearance:</b> Paste
<b>Color:</b> In accordance with product description	<b>Physical Form:</b> : Paste
<b>Odor:</b> Acetic Acid	<b>Odor Threshold:</b> Not available
<b>pH:</b> Not applicable	<b>Melting Point:</b> Not available
<b>Boiling Point:</b> Not applicable	<b>Decomposition:</b> Not available
<b>Flash Point:</b> >100 °C (closed cup)	<b>Evaporation Rate:</b> Not applicable
<b>OSHA Flammability Class:</b> Not classified as a flammability hazard	<b>Vapor Pressure:</b> Not applicable
<b>Vapor Density (air = 1):</b> Not available	<b>Density:</b> 1.007
<b>Specific Gravity (water = 1):</b> Not available	<b>Water Solubility:</b> Not available
<b>Log KOW:</b> Not available	<b>Coeff. Water/Oil Dist:</b> Not available
<b>KOC:</b> Not available	<b>Auto Ignition:</b> Not available
<b>Viscosity:</b> Not applicable	<b>VOC:</b> Not available
<b>Volatility:</b> Not available	<b>Molecular Formula:</b> Not available

## Section 10: Stability and Reactivity

Reactivity:	Not classified as a reactivity hazard.
Chemical Stability:	Stable at normal temperatures and pressure.
Possibility of Hazardous Reactions:	Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Acetic acid is formed upon contact with water or humid air. Adequate ventilation is required. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated temperatures.
Conditions to Avoid:	None known.
Incompatible Materials:	Oxidizing agents
<b>Hazardous Decomposition Products</b>	
Thermal decomposition	Formaldehyde

## Section 11: Toxicological Information

### Acute Toxicity

Not classified based on available information.

# SAFTEY DATA SHEET

Product Identifier: ASI 502 Black

Document #: SDS 006

Revision: 2

<b>Ingredients:</b>					
CAS	Component	Result	Species	Dose	Exposure
7631-86-9	Silicon dioxide	LD50 Oral	Rat	>3300 mg/kg	N/A
		LC50 Inhalation (dust/mist)	Rat	>2.08 mg/L	4 hr
		LD50 Dermal	Rabbit	>5000 mg/kg	N/A
13463-67-7	Titanium dioxide	LD50 Oral	Rat	>5000 mg/kg	N/A
		LC50 Inhalation (dust/mist)	Rat	>6.82 mg/L	4 hr
7429-90-5	Aluminum	LD50 Oral	Rat	>5000 mg/kg	N/A
		LC50 Inhalation (dust/mist)	Rat	>0.888 mg/L	4 hr
1333-86-4	Carbon black	LD50 Oral	Rat	>5000 mg/kg	N/A
		LC50 Inhalation (dust/mist)	Rat	>0.0046 mg/L	4 hr
		LD50 Dermal	Rabbit	>3000 mg/kg	N/A
<p><b>Information on Likely Routes of Exposure</b></p> <p><b>Inhalation:</b> Not classified based on available information.</p> <p><b>Ingestion:</b> Not classified based on available information.</p> <p><b>Skin Contact:</b> Not classified based on available information.</p> <p><b>Eye Contact:</b> Not classified based on available information.</p> <p><b>Immediate Effects:</b> Not classified based on available information.</p> <p><b>Delayed Effects:</b> No information is available.</p> <p><b>Medical Conditions Aggravated by Exposure:</b> No information is available.</p> <p><b>Irritation/Corrosivity Data:</b> Not classified based on available information.</p> <p><b>Respiratory Sensitization:</b> Not classified based on available information.</p> <p><b>Dermal Sensitization:</b> Not classified based on available information.</p> <p><b>Germ Cell Mutagenicity:</b> Not classified based on available information.</p> <p><b>Carcinogenicity:</b> Not classified based on available information.</p>					
<b>Component Carcinogenicity</b>					
CAS	Component	Result			

# SAFTEY DATA SHEET

Product Identifier: ASI 502 Black

Document #: SDS 006

Revision: 2

13463-67-7	Titanium dioxide	<b>IARC:</b> Group 2B (possibly carcinogenic to humans)
		<b>OSHA:</b> Not present at levels greater than or equal to 0.1% to be identified as a carcinogen or potential carcinogen
		<b>NTP:</b> Not present at levels greater than or equal to 0.1% to be identified as a carcinogen or potential carcinogen
1333-86-4	Carbon Black	<b>IARC:</b> Group 2B (possibly carcinogenic to humans)
		<b>OSHA:</b> Not present at levels greater than or equal to 0.1% to be identified as a carcinogen or potential carcinogen
		<b>NTP:</b> Not present at levels greater than or equal to 0.1% to be identified as a carcinogen or potential carcinogen
<p><b>Reproductive Toxicity:</b> Not classified based on available information.</p> <p><b>Specific Target Organ Toxicity – Single Exposure:</b> Not classified based on available information.</p> <p><b>Specific Target Organ Toxicity – Repeated Exposure:</b> Not classified based on available information.</p> <p><b>Aspiration Hazard:</b> Not classified based on available information.</p>		

Section 12: Ecological Information						
Ecotoxicity						
Component Analysis – Aquatic Toxicity						
CAS	Component	Aquatic	Result	Species	Dose	Exposure
13463-67-7	Titanium dioxide	Fish	LC50	Rainbow trout ( <i>Oncorhynchus mykiss</i> )	>100 mg/L	96 hr
		Invertebrates	EC50	Water flea ( <i>Daphnia magna</i> )	>100 mg/L	48 hr
		Algae	EC50	Marine diatom ( <i>Skeletonema costatum</i> )	>10,000 mg/L	72 hr
		Bacteria	EC50	N/A	>1000 mg/L	3 hr
7429-90-5	Aluminum	Fish	NOEC	Brown trout ( <i>Salmo trutta</i> )	>80 µg/L	96 hr
		Invertebrates	NOEC	Water flea ( <i>Daphnia magna</i> )	>0.135 mg/L	48 hr
		Algae	EC50	Green algae ( <i>Pseudokirchneriella subcapitata</i> )	>0.004 mg/L	72 hr
		Fish (Chronic toxicity)	NOEC	Fathead minnow ( <i>Pimephales promelas</i> )	7.1 mg/L	28 d
1333-86-4		Fish	LC0	Zebrafish ( <i>Danio rerio</i> )	1000 mg/L	96 hr

# SAFTEY DATA SHEET

Product Identifier: ASI 502 Black

Document #: SDS 006

Revision: 2

Carbon Black	Invertebrates	EC50	Water flea ( <i>Daphnia magna</i> )	>5600 mg/L	24 hr
	Algae	NOEC	Green algae ( <i>Desmodesmus subspicatus</i> )	10,000 mg/L	72 hr

**Persistence and Degradability:** No information available for the product.

**Bioaccumulative Potential:** No information available for the product.

**Mobility in Soil:** No information available for the product.

**Other adverse effects:** No information available for the product.

## Section 13: Disposal Considerations

### Disposal Methods

Resource Conservation and Recovery Act (RCRA): This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues: Dispose of in accordance with local regulations.

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

## Section 14: Transport Information

### International Regulation

**UNRTDG:** Not regulated as a dangerous good.

**IATA-DGR:** Not regulated as a dangerous good.

**IMDG-Code:** Not regulated as a dangerous good.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not applicable for product as supplied.

### Domestic Regulation

**49 CFR:** Not regulated as a dangerous good.

## Section 15: Regulatory Information

**EPCRA - Emergency Planning and Community Right-to-Know  
CERCLA Reportable Quantity**



# SAFTEY DATA SHEET

Product Identifier: ASI 502 Black

Document #: SDS 006

Revision: 2

Ingredients	CAS No.	Component RQ (lbs)	Calculated Product RQ (lbs)
Acetic Acid	64-19-7	5000	*
Acetic anhydride	108-24-7	5000	*

\* Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards:** No SARA Hazards

**SARA 313:** The following components are subject to reporting levels established by SARA Title III, Section 313:

Aluminum	7429-90-5	<=1.575%
----------	-----------	----------

**US State Regulations**

**Pennsylvania Right To Know**

Dimethyl siloxane, hydroxy-terminated	70131-67-8
Silicon dioxide	7631-86-9
Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9
Iron oxide	1332-37-2
Titanium dioxide	13463-67-7
Aluminium	7429-90-5
Pigment Blue 15	147-14-8
Acetic acid	64-19-7
Acetic anhydride	108-24-7

**California Prop. 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

**California List of Hazardous Substances**

Aluminium	7429-90-5
-----------	-----------

**California Permissible Exposure Limits for Chemical Contaminants**

Silicon dioxide	7631-86-9
Titanium dioxide	13463-67-7
Aluminum	7429-90-5

**The ingredients of this product are reported in the following inventories:**

TSCA:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS:	All ingredients listed or exempt.
IECSC:	All ingredients listed or exempt.
PICCS:	All ingredients listed or exempt.
DSL:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
REACH:	For purchases from American Sealants EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For

# SAFTEY DATA SHEET

Product Identifier: ASI 502 Black

Document #: SDS 006

Revision: 2

purchases from non-EU American Sealants legal entities with the intention to export into EEA please contact your DC representative/local office.

## Section 16: Other Information

Issue Date: 6/18/2015

Revision: 2


Revision Date: 8/8/2018

NFPA Ratings:

Health: 0

Fire: 1

Reactivity: 0



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = Not Significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, \* = Chronic

Key/Legend:

AICS (Australia); DSL (Canada); IECSC (China); REACH (European Union); ENCS (Japan); ISHL (Japan); KECI (Korea); NZIoC (New Zealand); PICCS (Philippines); TCSI (Taiwan); TSCA (USA); ACGIH – USA. ACGIH Threshold Limit Values (TLV); NIOSH REL – USA. NIOSH Recommended Exposure Limits; OSHA P0 – USA. OSHA – TABLE Z-1 Limits for Air Contaminants – 1910.1000; OSHA Z-1 – USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminates; OSHA Z-3 – USA. Occupational Exposure Limits (OSHA) – Table Z-3 Mineral Dusts; ACGIH / TWA – 8-hour, time-weighted average; NIOSH REL / TWA – Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek; NIOSH REL / ST – STEL – 15-minute TWA exposure that should not be exceeded at any time during a workday; OSHA P0 / TWA - 8-hour, time-weighted average; OSHA Z-1 / TWA - 8-hour, time-weighted average; OSHA Z-3 / TWA - 8-hour, time-weighted average

Disclaimer:

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations.

End of Document