



Product Instructions

Wildlife Slick Paint

Wildlife Invisible Slick Paint Exclusion Remedy



WISPER is an exterior grade mixture of epoxy type material, which when mixed and applied correctly, creates an excellent surface barrier to prevent roosting bats, swallow's mud nests, and other various wildlife from areas on structures. The most common application spots are covered areas under soffits, eaves, awnings, and overhangs.

Surfaces include log siding, vinyl, stucco, EIFS, brick, metal, Hardie siding, concrete, downspouts, plastic, and cinder blocks. Best results on vertical and angled areas. Raw wood should be sealed or painted prior to application to prevent over soaking. Species include swallows, bats, pigeons, squirrels, and raccoons with good results. No issues to-date with UV rays, heat, or cold.

APPLICATION DIRECTIONS

Contents are proportioned as needed to mix in a vessel. **MIX VERY WELL TOGETHER!** It can be brushed, rolled, or sprayed on. **USE ENTIRE CONTENTS OF BOTH BOTTLES.** Part A is the Resin and Part B is the Hardener.

Apply in weather above 40 degrees. Cure and dry times depend on the humidity, heat, and moisture outside where/when applied.

Make sure the areas you intend to apply on are as clean as they can be, and completely dry. Do not apply if rain is to be forecasted within 12 hours of application. Any dirt or debris on the surfaces will stay looking the same underneath the clear paint. Have an ample spot to use when applying, because once mixed, it has to be used within **ONE HOUR**. If multiple small areas are being painted, keep stirring the mixture so it doesn't settle. Tape off areas beforehand, like painting.

Naturally slick areas will generally only require one coat (metals, slick rock, and plastics). Surfaces like concrete, brick, painted wood, and other super grippy substrates may require two coats. Spots with unpainted raw wood, cedar, and other very porous wood may require many coats, as the wood wants to soak it in. These areas are not generally recommended for this product.

For exterior use only.

Per square foot coverage area depends on the substrates. It will be clear but will leave a bit of a wet look, or shiny look. For cleanup, use lacquer thinner. We recommend having lacquer thinner on hand in case of any spillage or clean up.

***Wear appropriate protective equipment. Avoid contact with skin, do not get in eyes, and do not ingest.
Wear appropriate respirator and gloves. Avoid exposure during pregnancy.***



Product Instructions

Wildlife Slick Paint

Wildlife Invisible Slick Paint Exclusion Remedy



WISPER is an exterior grade mixture of epoxy type material, which when mixed and applied correctly, creates an excellent surface barrier to prevent roosting bats, swallow's mud nests, and other various wildlife from areas on structures. The most common application spots are covered areas under soffits, eaves, awnings, and overhangs.

Surfaces include log siding, vinyl, stucco, EIFS, brick, metal, Hardie siding, concrete, downspouts, plastic, and cinder blocks. Best results on vertical and angled areas. Raw wood should be sealed or painted prior to application to prevent over soaking. Species include swallows, bats, pigeons, squirrels, and raccoons with good results. No issues to-date with UV rays, heat, or cold.

APPLICATION DIRECTIONS

Contents are proportioned as needed to mix in a vessel. **MIX VERY WELL TOGETHER!** It can be brushed, rolled, or sprayed on. **USE ENTIRE CONTENTS OF BOTH BOTTLES.** Part A is the Resin and Part B is the Hardener.

Apply in weather above 40 degrees. Cure and dry times depend on the humidity, heat, and moisture outside where/when applied.

Make sure the areas you intend to apply on are as clean as they can be, and completely dry. Do not apply if rain is to be forecasted within 12 hours of application. Any dirt or debris on the surfaces will stay looking the same underneath the clear paint. Have an ample spot to use when applying, because once mixed, it has to be used within **ONE HOUR**. If multiple small areas are being painted, keep stirring the mixture so it doesn't settle. Tape off areas beforehand, like painting.

Naturally slick areas will generally only require one coat (metals, slick rock, and plastics). Surfaces like concrete, brick, painted wood, and other super grippy substrates may require two coats. Spots with unpainted raw wood, cedar, and other very porous wood may require many coats, as the wood wants to soak it in. These areas are not generally recommended for this product.

For exterior use only.

Per square foot coverage area depends on the substrates. It will be clear but will leave a bit of a wet look, or shiny look. For cleanup, use lacquer thinner. We recommend having lacquer thinner on hand in case of any spillage or clean up.

***Wear appropriate protective equipment. Avoid contact with skin, do not get in eyes, and do not ingest.
Wear appropriate respirator and gloves. Avoid exposure during pregnancy.***

1160 South Street, Suffield, CT 06078 | (860)844-0101 | www.shopwcs.com



Product Instructions

Wildlife Slick Paint

Wildlife Invisible Slick Paint Exclusion Remedy



WISPER is an exterior grade mixture of epoxy type material, which when mixed and applied correctly, creates an excellent surface barrier to prevent roosting bats, swallow's mud nests, and other various wildlife from areas on structures. The most common application spots are covered areas under soffits, eaves, awnings, and overhangs.

Surfaces include log siding, vinyl, stucco, EIFS, brick, metal, Hardie siding, concrete, downspouts, plastic, and cinder blocks. Best results on vertical and angled areas. Raw wood should be sealed or painted prior to application to prevent over soaking. Species include swallows, bats, pigeons, squirrels, and raccoons with good results. No issues to-date with UV rays, heat, or cold.

APPLICATION DIRECTIONS

Contents are proportioned as needed to mix in a vessel. **MIX VERY WELL TOGETHER!** It can be brushed, rolled, or sprayed on. **USE ENTIRE CONTENTS OF BOTH BOTTLES.** Part A is the Resin and Part B is the Hardener.

Apply in weather above 40 degrees. Cure and dry times depend on the humidity, heat, and moisture outside where/when applied.

Make sure the areas you intend to apply on are as clean as they can be, and completely dry. Do not apply if rain is to be forecasted within 12 hours of application. Any dirt or debris on the surfaces will stay looking the same underneath the clear paint. Have an ample spot to use when applying, because once mixed, it has to be used within **ONE HOUR**. If multiple small areas are being painted, keep stirring the mixture so it doesn't settle. Tape off areas beforehand, like painting.

Naturally slick areas will generally only require one coat (metals, slick rock, and plastics). Surfaces like concrete, brick, painted wood, and other super grippy substrates may require two coats. Spots with unpainted raw wood, cedar, and other very porous wood may require many coats, as the wood wants to soak it in. These areas are not generally recommended for this product.

For exterior use only.

Per square foot coverage area depends on the substrates. It will be clear but will leave a bit of a wet look, or shiny look. For cleanup, use lacquer thinner. We recommend having lacquer thinner on hand in case of any spillage or clean up.

***Wear appropriate protective equipment. Avoid contact with skin, do not get in eyes, and do not ingest.
Wear appropriate respirator and gloves. Avoid exposure during pregnancy.***

1160 South Street, Suffield, CT 06078 | (860)844-0101 | www.shopwcs.com



Product Instructions

Wildlife Slick Paint

Wildlife Invisible Slick Paint Exclusion Remedy



WISPER is an exterior grade mixture of epoxy type material, which when mixed and applied correctly, creates an excellent surface barrier to prevent roosting bats, swallow's mud nests, and other various wildlife from areas on structures. The most common application spots are covered areas under soffits, eaves, awnings, and overhangs.

Surfaces include log siding, vinyl, stucco, EIFS, brick, metal, Hardie siding, concrete, downspouts, plastic, and cinder blocks. Best results on vertical and angled areas. Raw wood should be sealed or painted prior to application to prevent over soaking. Species include swallows, bats, pigeons, squirrels, and raccoons with good results. No issues to-date with UV rays, heat, or cold.

APPLICATION DIRECTIONS

Contents are proportioned as needed to mix in a vessel. **MIX VERY WELL TOGETHER!** It can be brushed, rolled, or sprayed on. **USE ENTIRE CONTENTS OF BOTH BOTTLES.** Part A is the Resin and Part B is the Hardener.

Apply in weather above 40 degrees. Cure and dry times depend on the humidity, heat, and moisture outside where/when applied.

Make sure the areas you intend to apply on are as clean as they can be, and completely dry. Do not apply if rain is to be forecasted within 12 hours of application. Any dirt or debris on the surfaces will stay looking the same underneath the clear paint. Have an ample spot to use when applying, because once mixed, it has to be used within **ONE HOUR**. If multiple small areas are being painted, keep stirring the mixture so it doesn't settle. Tape off areas beforehand, like painting.

Naturally slick areas will generally only require one coat (metals, slick rock, and plastics). Surfaces like concrete, brick, painted wood, and other super grippy substrates may require two coats. Spots with unpainted raw wood, cedar, and other very porous wood may require many coats, as the wood wants to soak it in. These areas are not generally recommended for this product.

For exterior use only.

Per square foot coverage area depends on the substrates. It will be clear but will leave a bit of a wet look, or shiny look. For cleanup, use lacquer thinner. We recommend having lacquer thinner on hand in case of any spillage or clean up.

***Wear appropriate protective equipment. Avoid contact with skin, do not get in eyes, and do not ingest.
Wear appropriate respirator and gloves. Avoid exposure during pregnancy.***

1160 South Street, Suffield, CT 06078 | (860)844-0101 | www.shopwcs.com